

# PosiTest<sup>®</sup> DFT

## Coating Thickness Gage

**New**

### *Ideal for...*

- Powder Coaters
- Paint Applicators
- Coating Inspectors
- Painting Contractors
- Automotive Refinishers

### *2 Models...*

**Ferrous** for STEEL

**Combo** for ALL METALS



simply  
measures

**DeFelsko<sup>®</sup>**  
*The Measure of Quality*

# PosiTest<sup>®</sup> DFT

## Coating Thickness Gage

Actual Size

### Two Models

- **PosiTest DFT Ferrous**  
measures non-magnetic coatings on steel.
- **PosiTest DFT Combo**  
measures both non-magnetic coatings on steel AND non-conductive coatings on aluminum, brass, etc. **Automatically** recognizes the substrate and takes a measurement.



### Features

- Fast, repeatable measurements
- No calibration required for most applications
- ZERO feature for rough or curved surfaces
- Handy RESET feature when no zero reference is available
- Strong, wear-resistant, ruby-tipped probe
- Audible and visible measurement indication
- V-groove in probe for positioning on cylindrical parts
- Mils/Microns switchable
- Basic instructions on the back of each gage

### Specifications

<b>Measurement Range</b>	0 – 40 mils	0 – 1000 $\mu$ m
<b>Accuracy</b>	$\pm(0.1 \text{ mils} + 3\%)$	$\pm(2\mu\text{m} + 3\%)$
<b>Size</b>	4 x 1.5 x 0.9 in.	100 x 38 x 23 mm
<b>Weight</b>	2.5 oz.	70 g



**Gage Comes Complete** with built-in probe, plastic shims, hard shell storage case, AAA battery, instructions and one (1) year warranty.

**Conforms to:** ISO 2178/2360/2808, prEN ISO 19840, ASTM B244/B499/B659/D1186/D7091-05/D1400/E376/G12, BS3900-C5, SSPC-PA2 and others. *Certificate of Calibration traceable to NIST available.*

© DeFelsko Corporation USA 2004. All Rights Reserved. Technical Data subject to change without notice. U.S. Patent # Re.35,703 • Printed in U.S.A. PDF.T.v.LW/W0404